

Model: FIM-40K



Equipment features

- Internally-scraping ice skate can help reduce energy consumption and prevent leakage of refrigerant
- Stainless steel materials, advanced processing equipment and heat treatment ensure the best heat transfer efficiency
- The design of large water receiving plate can prevent water leaking at the bottom of drum
- Photoelectric switch is directly installed in the bottom of evaporator
- Direct liquid feeding and dry evaporation —— simple, safe and reliable control.
- Integrated modular equipment installation is convenient for maintenance.

Parameters

Subject		Unit	Technical parameter
Power supply		Voltage/Phase/Frequency	380V/3P/50Hz
Refrigerant			R22 or R404A
Capacity		Kg/day	4000
Cooling way			Water cooling
Temperature	Ambient temperature	°C	35
	water inlet temperature	°C	20
Compressor	Manufacturer		Bitzer
	Refrigeration capacity	Kw	23.4
	Total running power	Kw	11.81
	Compressor COP/EER	Kw/kw	2.07
	Horse power	Hp	20
Operating power	Total running power	Kw	13.89
	Installment power	Kw	16
	Operating power of reducer	Kw	0.37
	Operating power of cold water pump	Kw	0.03
	Cooling water pump	Kw	1.5
	Fan of cooling tower	Kw	0.18
Dimension	Size of ice maker	(LxWxH)(mm)	1700x900x1200
	Size of cooling tower	(O.D.xH)(mm)	φ1170x1940
	Size of water feeding pipes of cooling tower		1/2"
	Size of cooling water pipes		2"
	Size of water feeding pipe		3/4"
	Size of ice outlet	mm	φ512
Weight of unit	Operating weight of flake ice maker	Kg	1000
	Operating weight of cooling tower	Kg	260
Water supply pressure requirement		Bar	1.5